

SBC-H4660VL

Half-Size ISA fanless AMD Geode GX CPU Board



Specifications

General Functions	
CPU	AMD Geode™ GX-466 CPU
CPU Speed	333MHz
Chipset	CS5536
BIOS	AWARD BIOS
System Memory	128MB DDR memory on board, One 200-pin SO-DIMM supports up to 512MB
VGA	Geode GX-466 Integrated VGA. Supports LCD 24-bit TTL interface
LAN	Realtek 8100C 10/100 Ethernet
3D Audio	Realtek ALC203 with AC97 Audio Codec
Super I/O	Winbond 83627EHG, 2 x Serial ports. COM2 is RS-232/422/485 selectable, 1 x Parallel port (SPP/EPP/ECP), 1 x FDD port, support up to two Floppy drives, 1 x PS2 KB/Mouse
IDE Interface	One EIDE Channel ()
SATA	Optional two SATA-150 ports, support RAID-0 & RAID-1 (ALI M5283)
SSD	50-pin Compact Flash type II socket
USB	Supports 4 USB 2.0 ports
Digital I/O	4x Digital Input, 4x Digital Output
Watchdog Timer	Programmable watchdog. Timeout event can be Reset system or NMI
Power Requirement	4A @ +5V(Max)
Dimensions	165 mm x 115 mm
Form Factor	ISA Bus Half-Size Single Board Computer